





บริษัท ดัคท์ เอ็กเซล จำกัด 1622/1 ถนนสุทธิสารวินิจฉัย แขวงห้วยขวาง เขตห้วยขวาง กรุงเทพฯ 10310 Tel. 086-490-3437 www.ductexcel.co.th E-Mail : center@ductexcel.co.th

Aluminium Foil-PVC (Flame-resistant) Smooth Flow Air Duct Model: A2SF



□ Color: White

☐ Size Availability: 4", 5", and 6"

☐ Product Design: The A2SF was designed with stronger material to reduce the

wrinkles inside the air duct to decrease air friction. The result is smoother air flow and less power of air ventilation fans and

yet easy to install.

☐ Purpose of use: Kitchen and bathroom ventilation duct, heating facilities and

hygienic cooling for condominiums, apartments and other

buildings

☐ Fire Classification: BS476 Class 0

Materials	Aluminum Foil, Polyester Film, and PVC (Flame resistant)
Structure	Laminated x 2ply
Wire	Copper Coated High Carbon Steel Bead Wire
Wire Spacing	19 mm
Thickness	180 um (micron)
Temperature Range	-30°C ~ +140°C
Air velocity	Max 25 m./sec
Working Pressure	Max 250 mm. WG (2500 Pa, or 10" W.G.)
Standard Length	8 meters

Technical specifications are subject to change without notice.